

SAFETY DATA SHEET

In accordance with GB REACH UK SI 2020 No. 1577

Product: V-AIR FLOW REFILL-BERGAMOT & SANDALWOOD V-FLOW-BER-EU

Version: 1

Section 1. Identification of the substance or the mixture and of the supplier

1.1 Product Identifier

Product identifier: V-AIR FLOW REFILL-BERGAMOT & SANDALWOOD V-FLOW-BER-EU(Contains:4-tert-Butylcyclohexyl acetate)

Other identifiers: VA-25-007-FLOW

Unique Formula Identifier (UFI): 6D51-X0AT-R00N-HYE4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product uses: Air Freshener,For Professional use only.

Uses advised against: Use only for intended applications

1.3 Details of the supplier of the safety data sheet

Company name: Vectair Systems Ltd

Company address: Unit 3, Trident Centre, Armstrong Road, Basingstoke, Hampshire, RG24 8NU, UK

Contact: Product Development

E-Mail address: prod-dev@vectairsystems.com

Company phone: +44 (0) 1256 319500 (Office Hours 09:00 to 17:00)

1.4 Emergency telephone number

Emergency phone: INFOTRAC +1 800 535 5053 INTERNATIONAL +1 352 323 3500

Section 2. Hazards identification

2.1 Classification of the substance or mixture

Classification under GB GHS UK SI 2020 No. 1567

Class and category of danger: Sensitization - Skin Category 1
Hazardous to the Aquatic Environment - Long-term Hazard Category 3
H317, May cause an allergic skin reaction.
H412, Harmful to aquatic life with long lasting effects.

2.2 Label elements

Classification under GB GHS UK SI 2020 No. 1567

Signal word: Warning

Hazard statements: H317, May cause an allergic skin reaction.
H412, Harmful to aquatic life with long lasting effects.

Supplemental Information: None

SAFETY DATA SHEET

In accordance with GB REACH UK SI 2020 No. 1577

Product: V-AIR FLOW REFILL-BERGAMOT & SANDALWOOD V-FLOW-BER-EU

Version: 1

Precautionary statements:

P273, Avoid release to the environment.

P280, Wear protective gloves/eye protection/face protection.

P302/352, IF ON SKIN: Wash with plenty of soap and water.

P333/313, If skin irritation or rash occurs: Get medical advice/attention.

P501, Dispose of contents/container to approved disposal site, in accordance with local regulations.

Pictograms:



Unique Formula Identifier (UFI): 6D51-X0AT-R00N-HYE4

2.3 Other hazards

Other hazards: Hydrocarbon Concentration %: 0.0000%

Section 3. Composition / information on ingredients

3.2 Mixtures

Contains:

Name	CAS	EC	GB REACH Registration No.	%	GB GHS UK SI 2020 No. 1567
Ethylene brassylate	105-95-3	203-347-8		1-<5%	Aquatic Chronic 3; H412,-
4-tert-Butylcyclohexyl acetate	32210-23-4	250-954-9		1-<5%	Skin Sens. 1B;H317,-
2-Isobutyl-4-methyltetrahydro-2H-pyran-4-ol	63500-71-0	405-040-6		1-<5%	Eye Irrit. 2;H319,-
Terpinyl acetate (Isomer mixture)	8007-35-0	232-357-5		1-<5%	Aquatic Chronic 2; H411,-
Tricyclodecanyl acetate	5413-60-5	226-501-6		1-<5%	Aquatic Chronic 1; H410,-
Diethyl malonate	105-53-3	203-305-9		1-<5%	Eye Irrit. 2;H319,-

GB workplace exposure limits:

Not Applicable

Substances that are persistent, bioaccumulative and toxic or very persistent and very bioaccumulative, greater than 0.1%:

Not Applicable

SAFETY DATA SHEET

In accordance with GB REACH UK SI 2020 No. 1577

Product: V-AIR FLOW REFILL-BERGAMOT & SANDALWOOD V-FLOW-BER-EU

Version: 1

Section 4. First-aid measures

4.1 Description of first aid measures

Inhalation: Remove from exposure site to fresh air, keep at rest, and obtain medical attention.
Eye exposure: Flush immediately with water for at least 15 minutes. Contact physician if symptoms persist.
Skin exposure: IF ON SKIN: Wash with plenty of soap and water.
Ingestion: Rinse mouth with water and obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

None expected, see Section 4.1 for further information.

Section 5: Firefighting measures

5.1 Extinguishing media

Suitable media: Carbon dioxide, Dry chemical, Foam.

5.2 Special hazards arising from the substance or mixture

In case of fire, may be liberated: Carbon monoxide, Unidentified organic compounds.

5.3 Advice for fire fighters:

In case of insufficient ventilation, wear suitable respiratory equipment.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Avoid inhalation. Avoid contact with skin and eyes. See protective measures under Section 7 and 8.

6.2 Environmental precautions:

Keep away from drains, surface and ground water, and soil.

6.3 Methods and material for containment and cleaning up:

Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Contain spillage immediately by use of sand or inert powder. Dispose of according to local regulations.

6.4 Reference to other sections:

Also refer to sections 8 and 13.

SAFETY DATA SHEET

In accordance with GB REACH UK SI 2020 No. 1577

Product: V-AIR FLOW REFILL-BERGAMOT & SANDALWOOD V-FLOW-BER-EU

Version: 1

Section 7. Handling and storage

7.1 Precautions for safe handling:

Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Use personal protective equipment as required. Use in accordance with good manufacturing and industrial hygiene practices. Use in areas with adequate ventilation. Do not eat, drink or smoke when using this product.

7.2 Conditions for safe storage, including any incompatibilities:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

7.3 Specific end use(s):

Air Freshener, For Professional use only.: Use in accordance with good manufacturing and industrial hygiene practices.

Section 8. Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limits: Not Applicable

8.2 Exposure Controls

Eye / Skin Protection

Wear protective gloves/eye protection/face protection

Respiratory Protection

Under normal conditions of use and where adequate ventilation is available to prevent build up of excessive vapour, this material should not require special engineering controls. However, in conditions of high or prolonged use, or high temperature or other conditions which increase exposure, the following engineering controls can be used to minimise exposure to personnel: a) Increase ventilation of the area with local exhaust ventilation. b) Personnel can use an approved, appropriately fitted respirator with organic vapour cartridge or canisters and particulate filters. c) Use closed systems for transferring and processing this material.

Also refer to Sections 2 and 7.

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	orange Solid
Odour:	Characteristic
Odour threshold:	Not determined
pH:	Not determined
Melting point / freezing point:	Not determined
Initial boiling point / range:	> 100 °C
Flash point:	> 100 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined

SAFETY DATA SHEET

In accordance with GB REACH UK SI 2020 No. 1577

Product: V-AIR FLOW REFILL-BERGAMOT & SANDALWOOD V-FLOW-BER-EU

Version: 1

Upper/lower flammability or explosive limits:	Product does not present an explosion hazard
Vapour pressure:	Not determined
Vapour density:	Not determined
Relative density:	Not determined
Solubility(ies):	Not determined
Partition coefficient: n-octanol/water:	Not determined
Auto-ignition temperature:	> 200 °C
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Not expected
Oxidising properties:	Not expected

9.2 Other information: None available

Section 10. Stability and reactivity

10.1 Reactivity:

Presents no significant reactivity hazard, by itself or in contact with water.

10.2 Chemical stability:

Good stability under normal storage conditions.

10.3 Possibility of hazardous reactions:

Not expected under normal conditions of use.

10.4 Conditions to avoid:

Avoid extreme heat.

10.5 Incompatible materials:

Avoid contact with strong acids, alkalis or oxidising agents.

10.6 Hazardous decomposition products:

Not expected.

Section 11. Toxicological information

11.1 Information on toxicological effects

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in GB GHS UK SI 2020 No. 1567.

Acute Toxicity:	Based on available data the classification criteria are not met.
Acute Toxicity Oral	>5000
Acute Toxicity Dermal	Not Applicable
Acute Toxicity Inhalation	Not Available
Skin corrosion/irritation:	Based on available data the classification criteria are not met.
Serious eye damage/irritation:	Based on available data the classification criteria are not met.
Respiratory or skin sensitisation:	

SAFETY DATA SHEET

In accordance with GB REACH UK SI 2020 No. 1577

Product: V-AIR FLOW REFILL-BERGAMOT & SANDALWOOD V-FLOW-BER-EU

Version: 1

Sensitization - Skin Category 1

Germ cell mutagenicity: Based on available data the classification criteria are not met.
Carcinogenicity: Based on available data the classification criteria are not met.
Reproductive toxicity: Based on available data the classification criteria are not met.
STOT-single exposure: Based on available data the classification criteria are not met.
STOT-repeated exposure: Based on available data the classification criteria are not met.
Aspiration hazard: Based on available data the classification criteria are not met.

Information about hazardous ingredients in the mixture

Not Applicable

Refer to Sections 2 and 3 for additional information.

Section 12. Ecological information

12.1 Toxicity:

Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability: Not available

12.3 Bioaccumulative potential: Not available

12.4 Mobility in soil: Not available

12.5 Results of PBT and vPvB assessment:

This substance does not meet the PBT/vPvB criteria of GB REACH UK SI 2020 No. 1577.

12.6 Other adverse effects: Not available

Section 13. Disposal considerations

13.1 Waste treatment methods:

Dispose of in accordance with local regulations. Avoid disposing into drainage systems and into the environment. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Section 14. Transport information

	14.1 UN number:	14.2 UN Proper Shipping Name:	14.3 Transport hazard class (es):	Sub Risk:	14.4 Packing Group:
UN Model Regulations	Not classified	-	-	-	-
IMDG	Not classified	-	-	-	-
ADR,RID,ADN	Not classified	-	-	-	-
ICAO TI	Not classified	-	-	-	-

14.5 Environmental hazards: Not environmentally hazardous for transport

SAFETY DATA SHEET

In accordance with GB REACH UK SI 2020 No. 1577

Product: V-AIR FLOW REFILL-BERGAMOT & SANDALWOOD V-FLOW-BER-EU

Version: 1

14.6 Special precautions for user: None additional

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not classified

Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SDS Reference No.: SD-000037S

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out for this product.

Section 16. Other information

Concentration % Limits: SS 1=33.33% EH C3(GB)=11.96%

Total Fractional Values: SS 1=3.00 EH C3(GB)=8.36

Key to revisions:

Not applicable

Key to abbreviations:

Abbreviation	Meaning
Aquatic Chronic 1	Hazardous to the Aquatic Environment - Long-term Hazard Category 1
Aquatic Chronic 2	Hazardous to the Aquatic Environment - Long-term Hazard Category 2
Aquatic Chronic 3	Hazardous to the Aquatic Environment - Long-term Hazard Category 3
Eye Irrit. 2	Eye Damage / Irritation Category 2
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
P261	Avoid breathing vapour or dust.
P264	Wash hands and other contacted skin thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection/face protection.
P302/352	IF ON SKIN: Wash with plenty of soap and water.
P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333/313	If skin irritation or rash occurs: Get medical advice/attention.
P337/313	If eye irritation persists: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P501	Dispose of contents/container to approved disposal site, in accordance with local regulations.

SAFETY DATA SHEET

In accordance with GB REACH UK SI 2020 No. 1577

Product: V-AIR FLOW REFILL-BERGAMOT & SANDALWOOD V-FLOW-BER-EU

Version: 1

Skin Sens. 1B	Sensitization - Skin Category 1B
---------------	----------------------------------

The information in this safety data sheet is to the best of our knowledge true and accurate but all data, instructions, recommendations and/or suggestions are made without guarantee.